



Clarity Matrix G3 LX46X

LCD Video Wall System

The Clarity® Matrix® G3 LX46X is a 46" LCD video wall display with an extreme narrow tiled bezel width of 1.7mm that provides a nearly seamless digital canvas, outstanding tiled visual performance, extended operation and requires minimal installation space. Designed for 24x7 operation, the Clarity Matrix G3 LX46X features 500 nits brightness, LED backlight technology and Full HD resolution— making it the ideal video wall for high-impact, mission-critical applications.



SPECIFICATION	DETAIL
Technology	Commercial-grade LCD
Per Panel Dimensions (Including Mount)	40.3 x 22.7 x 3.6in 1019 x 573 x 91mm
Diagonal	46in 1168mm
Native Resolution Panels	1920 x 1080
Aspect Ratio	16:9
Tiled Bezel Width	0.06in 1.7mm
Power Consumption, Typical (watts)	114/Display
Power supply voltage	100-230V AC ± 10%, 50 to 60 Hz
Power Status	Diagnostics LEDs, health monitoring and alerts
Per Panel Weight (Including Mount)	41lb 19kg
Shipping weight	142lb 64.4kg
Mounted Depth	3.6in 91.44mm (wall to front of display)
Brightness (typ)	500 cd/m ² or nits
Contrast ratio (full field)	4000:1
Response Time (typ)	8 ms
Full viewing angle	178°
Data Inputs	4 HDMI 2.0, 1 DisplayPort 1.2
Video Extension built-in	200ft 60m over STP CAT6
Control	IR Remote, RS232, Ethernet, WallDirector™ Software

Backlight control	Individual and wall control
Backlight sensing and reporting	At display level
Display module position sensing	Auto-sensing integrated
Backlight life (1/2 brightness)	50,000 Hrs
Power Supply	Offboard Redundant Optional Hot Swap
Wall Mount	Planar® EasyAxis™ Mounting System VESA Mount (optional)
Acoustic Noise	Fanless operation at the Display
Heat load	580 BTU/hr
Operating Temperature/Humidity (degrees F/C, relative humidity)	5° to 40° C / 20-90% RH 41° to 104° F / 20-90% RH
Orientation	Landscape or Portrait
Safety regulations	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
Touch Technology	Clarity Matrix MultiTouch (optional)
Protection	Planar® ERO-LCD™ (Extended Ruggedness and Optics™) Technology (optional)
Fiber Video Extension Module Option	1 RU rack mount module drives up to 4 displays
Fiber Video Extension Module Outputs	SFP multi-mode transceivers supports distances up to 300m from wall Single-mode compatible up to 10k from the wall

For more information, please visit www.leyard.com

Specifications are subject to change without notice.

Specification Report Date: 11/16/2018

© Copyright 2018 Leyard All rights reserved