



Clarity Matrix G3 MX55U

LCD Video Wall System

The Clarity® Matrix® G3 MX55U is a 55" LCD video wall display with a tiled bezel width of 3.7mm that provides a nearly seamless digital canvas, outstanding tiled visual performance, extended operation and requires minimal installation space. Designed for 24x7 operation, the Clarity Matrix G3 MX55U features 800 nits brightness, LED backlight technology and Full HD resolution— making it the ideal video wall for high-impact, mission-critical applications.



| SPECIFICATION | DETAIL |
|---|--|
| Technology | Commercial-grade LCD |
| Per Panel Dimensions (Including Mount) | 47.78 x 26.94 x 3.6in 1213.6 x 684.3 x 91.4mm |
| Diagonal | 55in 1397mm |
| Native Resolution Panels | 1920 x 1080 |
| Aspect Ratio | 16:9 |
| Tiled Bezel Width | 0.15in 3.7mm |
| Power Consumption, Typical (watts) | 237/Display |
| Power supply voltage | 100-230V AC ± 10%, 50 to 60 Hz |
| Power Status | Diagnostics LEDs, health monitoring and alerts |
| Per Panel Weight (Including Mount) | 59lb 26.76kg |
| Shipping weight | 150lb 68.04kg |
| Mounted Depth | 3.6in 91.44mm (wall to front of display) |
| Brightness (typ) | 800 cd/m ² or nits |
| Contrast ratio (full field) | 4000:1 |
| Response Time (typ) | 8 ms |
| Full viewing angle | 178° |
| Data Inputs | 4 HDMI 2.0, 1 DisplayPort 1.2 |
| Video Extension built-in | 200 ft./60m over STP CAT6 |
| Control | IR Remote, RS232, Ethernet, WallDirector™ Software |

| | |
|--|--|
| Backlight control | Individual and wall control |
| Backlight sensing and reporting | At display level |
| Display module position sensing | Auto-sensing integrated |
| Backlight life (1/2 brightness) | 50,000 Hrs |
| Power Supply | Offboard Redundant Optional Hot Swap |
| Wall Mount | Planar® EasyAxis™ Mounting System VESA Mount (optional) |
| Acoustic Noise | Fanless operation at the Display |
| Heat load | 832BTU/hr |
| Operating Temperature/Humidity (degrees F/C, relative humidity) | 5° to 40° C / 20-90% RH 41° to 104° F / 20-90% RH |
| Orientation | Landscape or Portrait |
| Safety regulations | Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS |
| Touch Technology | Clarity Matrix MultiTouch (optional) |
| Protection | Planar® ERO™ (Extended Ruggedness and Optics™) Technology (optional) |
| Fiber Video Extension Module Option | 1 RU rack mount module drives up to 4 displays |
| Fiber Video Extension Module Outputs | SFP multi-mode transceivers supports distances up to 300m from wall Single-mode compatible up to 10k from the wall |

For more information, please visit www.leyard.com

Specifications are subject to change without notice.

Specification Report Date: 8/15/2018

© Copyright 2018 Leyard All rights reserved