

## Planar 3G-SDI OPS

### OPS Module

Display broadcast-quality video with 3G/HD/SD-SDI input and daisy chain. Supports a wide range of SDI input signals from 480i to 1080p. Compatible with Intel's Open Pluggable Specification (OPS), Planar's selection of expansion modules can be integrated seamlessly into Planar displays with OPS slots. The compact size of OPS compatible modules is small enough to be installed discreetly and securely to the back of the Planar display.



SPECIFICATION	DETAIL
<b>Inputs</b>	SDI in
<b>Outputs</b>	SDI out
<b>Supported Resolutions</b>	SD 525i, SDI 625i, HD 720p 50/60Hz, HD 1080i 50/60Hz, HD 1080p 24/25/30/50/60Hz
<b>Supported Video Standards</b>	20 bit 4:2:2
<b>Supported Planar Displays</b>	EP Series, UltraRes Series, and RA Series
<b>Dimensions (W x H x D)</b>	7.9" x 4.6" x 1.2" (200mm x 118mm x 30mm)
<b>Weight</b>	1.3 lb (0.6 kg)
<b>Shipping weight</b>	1.5 lb (0.7 kg)
<b>Operating Temperature</b>	0-40°C (32 -104°F)
<b>Humidity</b>	10 to 90%
<b>Safety regulations</b>	FCC Class A, CE

For more information, please visit [www.leyard.com](http://www.leyard.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/24/2019*

*© Copyright 2019 Leyard All rights reserved*