



PLL1911M

19" LCD Monitor

The Planar® PLL1911M 19" LED LCD monitor features a 5:4 aspect ratio, dual input, integrated speakers, and an adjustable stand that makes it perfect for business applications.



SPECIFICATION	DETAIL
Product Name	PLL1911M
Planar Part Number	997-7451-00
Viewable Size	19" diagonal (14.81" horizontal x 11.85" vertical)
Aspect Ratio	5:4
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	5 ms (GTG)
Brightness (Typical)	250 cd/m ²
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1280 x 1024 SXGA
Tilt Range	-5° to +19°
Palette	16.7 million colors
Pixel Pitch	0.294 mm
Refresh Rate	55~76 Hz (60 Hz recommended)
Dimensions (W x H x D)	16.0" x 16.7" x 8.5" (height can be adjusted to 20.3"); 406.4 mm x 424.2 mm x 215.9 mm (adjusted to 515.6 mm)
Dimensions without Stand	16.0" x 13.8" x 2.4" (406.4 mm x 350.5 mm x 61.0 mm)
Panel Depth	2.4" (61.0 mm)
Display Weight	8.2 lb (3.7 kg) , 6.2 lb (2.8 kg) without base & stand
Shipping weight	10.6 lb (4.8 kg)
Video Inputs	Digital (DVI-D w/HDCP), Analog (VGA)

HDCP	Yes
External Connections	(1) DVI 24-pin connector, (1) Analog VGA D-sub 15-pin video display, (1) 1/8 inch audio input jack
Audio Output	1w x 2
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	Internal
Power Consumption (max)	21W typical (standby 0.5W)
Power Requirements	AC 100/240 VAC
Operating Temperature	0° to +40°C (32° to 104°F)
Humidity	10 - 90% RH (non-condensing)
Mount	Built-in 100 mm VESA, back
Product Approvals	FCC-B, CE, UL/cUL, RoHS
Recommended Usage	Up to 16 hours per day
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
Options / Features	Height adjustable stand, Supports Portrait, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
In the Box	PLL1911M 19" LED LCD Monitor, Power Cord, VGA Cable, DVI Cable, Audio Cable, User's Guide
Humidity	10 - 90% RH (non-condensing)

For more information, please visit www.leyard.com

Specifications are subject to change without notice.

Specification Report Date: 5/24/2019

© Copyright 2019 Leyard All rights reserved