



# Clarity Matrix G3 MX55M

## LCD Video Wall System

The Clarity® Matrix® G3 MX55M is a 55" LCD video wall display with a tiled bezel width of 0.88 mm that provides a nearly seamless digital canvas, outstanding tiled visual performance, extended operation and requires minimal installation space. The reduced weight of Clarity Matrix G3 MX55M facilitates increased durability and easier installation. User-selectable local dimming delivers the highest contrast ratio and black-level uniformity, for brighter whites and darker, more consistent, blacks. Designed for 24x7 operation, the Clarity Matrix G3 MX55M features 700 nits brightness, LED backlight technology and Full HD resolution—making it the ideal video wall for high-impact, mission-critical applications.



SPECIFICATION	DETAIL
<b>Technology</b>	Commercial-grade LCD
<b>Per Panel Dimensions (Including Mount)</b>	47.6 x 26.8 x 3.5 in   1210.5 x 681 x 90 mm
<b>Diagonal</b>	55in   1397mm
<b>Native Resolution Panels</b>	1920 x 1080
<b>Aspect Ratio</b>	16:9
<b>Tiled Bezel Width</b>	0.88 mm   .04 in
<b>Thermal Expansion Gap Required</b>	0.4 mm   .02 in
<b>Power Consumption (max/display)</b>	235W
<b>Power supply voltage</b>	100-230V AC ± 10%, 50 to 60 Hz
<b>Power Status</b>	Diagnostics LEDs, health monitoring and alerts
<b>Per Panel Weight (Including Mount)</b>	47 lbs   21.1 kg (Landscape) 49 lbs   22.4 kg (Portrait)
<b>Shipping weight</b>	106 lbs   48.1 kg (single pack) / 170 lbs   77.1 kg (dual pack)
<b>Mounted Depth</b>	3.6in   91.44mm (wall to front of display)
<b>Brightness (typ)</b>	700 cd/m <sup>2</sup> or nits
<b>Contrast ratio (full field)</b>	10000:1 (local dimming on) 1100:1 (local dimming off)
<b>Response Time (typ)</b>	8 ms
<b>Full viewing angle</b>	178°
<b>Video Inputs (Controller)</b>	4x HDMI 2.0 (w/ HDCP 2.2), 1x DisplayPort 1.2

<b>Video Outputs (Controller)</b>	9-Output Controller: 9x RJ45 8P8C, 1x DisplayPort 1.2   4-Output Controller: 4x RJ45 8P8C, 1x DisplayPort 1.2
<b>Video Extension built-in</b>	200ft   60m over STP CAT6
<b>Control</b>	IR Remote Control, RS-232, USB, Network, Leyard WallDirector Software
<b>Sync</b>	Mini BNC In/Out
<b>Backlight control</b>	Individual and wall control
<b>Backlight sensing and reporting</b>	At display level
<b>Display module position sensing</b>	Auto-sensing integrated
<b>Backlight life (1/2 brightness)</b>	50,000 Hrs
<b>Power Supply</b>	Offboard   Redundant Optional   Hot Swap
<b>Wall Mount</b>	Planar® EasyAxis™ Mounting System   VESA Mount (optional)
<b>Acoustic Noise</b>	Fanless operation at the Display
<b>Heat Load (max/display)</b>	802 BTU/hr
<b>Operating Temperature/Humidity (degrees F/C, relative humidity)</b>	5° to 40° C / 20-90% RH   41° to 104° F / 20-90% RH
<b>Orientation</b>	Landscape or Portrait
<b>Safety regulations</b>	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
<b>Touch Technology</b>	Clarity Matrix MultiTouch (optional)
<b>Protection</b>	Planar® ERO-LCD™ (Extended Ruggedness and Optics™) Technology (optional)
<b>Fiber Video Extension Module Option</b>	1 RU rack mount module drives up to 4 displays
<b>Fiber Video Extension Module Outputs</b>	SFP multi-mode transceivers supports distances up to 300m from wall   Single-mode compatible up to 10k from the wall

For more information, please visit [www.leyard.com](http://www.leyard.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 7/23/2019*

*© Copyright 2019 Leyard All rights reserved*