



Leyard VSI2.5

Indoor Rental & Staging LED Video Wall Displays

The Leyard® VSI2.5 is an indoor rental and staging LED video wall display that takes event viewing experiences to the next level. With high brightness and contrast ratio, it delivers crisp images that audiences love. Magnetically-attachable, lightweight tiles with ratcheting quick-locks enable fast, single-person installation and disassembly. Designed with corner protection and an anti-collision edge to withstand frequent assembly and teardown, it is the LED display stagers demand.



| SPECIFICATION | DETAIL |
|--------------------------------------|---|
| Part Number | VSI2.5 |
| Pixel Pitch | 2.5mm |
| Cabinet Resolution | 200x200 |
| Pixel Density | 160000/sq m 14864/sq ft |
| LED Cabinet Size (W x H x D) | 500 x 500 x 77mm 19.69 x 19.69 x 3.03in |
| Cabinet Diagonal | 707mm 27.8in |
| Cabinet Area | 0.25m ² 2.69 ft ² |
| Modules/Cabinet (W x H) | 2x2 |
| Module Size | 250 x 250 mm 9.84 x 9.84 in |
| Power Consumption, Maximum (watts) | 155/Cabinet 620/sq m |
| Line Voltage | 100~240V AC, 50/60Hz |
| Cabinet Weight (per display) | 7kg 15.43lb |
| Cabinet Weight (per m ²) | 28kg 61.73lb |
| Brightness | 1000 |
| Contrast Ratio | 4000:1 |
| LED Refresh Rate | 3840Hz |
| Color Temperature, Adjustable (k) | 3000 - 10000 |

| | |
|--|--------------------------------|
| Viewing Angle, Horizontal | 140° |
| Viewing Angle, Vertical | 140° |
| Service Access | Front (module) / Rear |
| LED Lifetime: Typical | 75000 hr |
| Environmental | Indoor |
| Protection | IP40 |
| Operating Temperature/Humidity (degrees F/C, relative humidity) | -20° to 40° C 4° to 104° F |
| Storage Temperature/Humidity (degrees F/C, relative humidity) | -35° to 60° C -31° to 140° F |
| Installation, Service | Hanging, Stacking |
| Controller | S6F Controller |

For more information, please visit www.leyard.com

Specifications are subject to change without notice.

Specification Report Date: 12/12/2019

© Copyright 2019 Leyard All rights reserved